





















Kabel für Aufnehmer mit Ladungsausgang Cables for Transducers with Charge Output

Typ Model	Länge Length	Ende 1 End 1	Ende 2 End 2	Max. Temp. Max. Temp.	Kapazität Capacitance	Kabel-Ø Cable-Ø	Kabelmantel Cable Jacket
009	1.5 m	 UNF 10-32 (m)	 UNF 10-32 (m)	80 °C	135 pF	2.2 mm	PVC
009/T	1.5 m			200 °C	150 pF	2.0 mm	Teflon
010/5	5.0 m			80 °C	450 pF	3.8 mm	PVC
010/10	10.0 m			80 °C	900 pF	3.8 mm	PVC
011	1.5 m	 UNF 10-32 (m)	 BNC (m)	80 °C	135 pF	2.2 mm	PVC
012	1.5 m	 UNF 10-32 (m)	 TNC (m)	80 °C	135 pF	2.2 mm	PVC
013	1.5 m	 UNF 10-32 (m)	 M3 Subminiature (m)	80 °C	135 pF	2.2 mm	PVC
013/T	1.5 m	 UNF 10-32 (m)	 M3 Subminiature (m)	80 °C	150 pF	1.0 mm	PTFE

Kabel für Aufnehmer mit integriertem Verstärker (IEPE) Cables for Transducers with integrated amplifier (IEPE)

Typ Model	Länge Length	Ende 1 End 1	Ende 2 End 2	Max. Temp. Max. Temp.	Kabel-Ø Cable-Ø	Kabelmantel Cable Jacket
050	1.5 m	 UNF 10-32 (m)	 UNF 10-32 (m)	80 °C	2.8 mm	PVC
051	1.5 m	 UNF 10-32 (m)	 BNC (m)	80 °C	2.8 mm	PVC
051/5	5.0 m			80 °C	2.8 mm	PVC
051/10	10.0 m			80 °C	2.8 mm	PVC
052	1.5 m	 UNF 10-32 (m)	 TNC (m)	80 °C	2.8 mm	PVC
053	1.5 m	 BNC (m)	 TNC (m)	80 °C	2.8 mm	PVC
054	1.5 m	 UNF 10-32 (m)	 M3 Subminiature (m)	120 °C	1.0 mm	PUR

Kabel für ausgewählte Sensoren

Cables for Specific Sensors

Typ Model	Länge Length	Ende 1 End 1	Ende 2 End 2	Max. Temp. Max. Temp.	Schutzgrad Prot. Grade	Kabel-Ø Cable-Ø	Kabelmantel Cable Jacket
084G 084W für: KSI8xV	5.0 m	 Binder 713 (f) gerade/gewinkelt Binder 713 (f) straight/angled	 offen - pigtail	80 °C	IP67	6.0 mm	PUR
085G 085W für: KS80, KS81, KS48	5.0 m	 Binder 713 (f) gerade/gewinkelt Binder 713 (f) straight/angled	 offen - pigtail	80 °C	IP67	6.0 mm	PUR
086G 085W für: KS80, KS81, KS48	5.0 m	 Binder 713 (f) gerade/gewinkelt Binder 713 (f) straight/angled	 BNC (m)	80 °C	IP67	6.0 mm	PUR
087 für: KS813, KB103V	5.0 m	 Binder 718 (f)	 offen - pigtail	80 °C	IP67	3.9 mm	PVC
088 für: KS813, KB103V	5.0 m	 Binder 718 (f)	 Binder 711 (m)	80 °C	IP67	3.9 mm	PVC
091 für: KS943	3.0 m	 Binder 707 (m)	 Binder 711 (m)	80 °C	-	3.0 mm	PVC
091/T für: KS943	3.0 m	 Binder 707 (m)	 Binder 711 (m)	120 °C	-	1.1 mm	PUR